





Treadwall® Kore4/10 Rotating Walls



The Kore4/10 unit is a Treadwall designed for solely residential, climbing-focused use. It is only used at overhanging angles, and sold as a Base unit with options or the complete Pro package. The wall's rotation is powered by the climber's weight - there are no motors. The wall angle is adjusted using the new and enhanced hand crank system, which allows on-going adjustments through three broad ranges. A patented auto-stop mechanism gently brakes the wall when the climber's feet reach the bottom, matching the wall's movement to the climber, and a lever on the right side adjusts speed or resistance. The Kore4/10 is designed to fit under a 10 foot ceiling. See Kore4/11 units for higher ceilings. There is no Kore6/12 option.



SPECIFICATIONS:

Weight: 700 pounds.

Construction: Steel framework with custom-machined wood panels.

Placement: Inside standard - outside with exterior upgrade.

Width of climbing surface: 4 feet.

Total length of climbing surface: 18 feet.

Number of possible hold placements: 180.

Angle range: negative 5 degrees to negative 35 degrees.

Mode of control: Electro-hydraulic braking and resistance.

Electrical requirements: 9 VDC (1500ma) Plug-in transformer (supplied) or battery used.

Electronic Display: Measures distance (feet or meters), time and calories. Time and distance goals can be pre-set.

Color - frame: Anthracite Gray is standard. Custom colors available.

Color - panels: Natural Wood


Holds: Set of 36 custom training holds in 3 color groups, with optional 13 ladder Line^(tm) holds.

Maximum hold size: 2.5 inches high by 6 inches wide.


Floor Mat: 4 feet x 8 feet custom mat, 1.25 inches dual foam, black 14 oz. vinyl cover.

Warranty: Two years parts. See full warranty for details.

Treadwall® Kore4/11 Rotating Walls



The Kore4/11 unit is a Treadwall designed for solely residential, climbing-focused use. It is only used at overhanging angles, and sold as a Base unit with options or the complete Pro package. The wall's rotation is powered by the climber's weight - there are no motors. The wall angle is adjusted using the new and enhanced hand crank system, which allows on-going adjustments through three broad ranges. A patented auto-stop mechanism gently brakes the wall when the climber's feet reach the bottom, matching the wall's movement to the climber, and a lever on the right side adjusts speed or resistance. The Kore4/11 is designed to fit under an 11 foot ceiling. See Kore4/10 units for lower ceilings. There is no Kore4/12 option.



SPECIFICATIONS:

Weight: 800 pounds.

Construction: Steel framework with custom-machined wood panels.

Placement: Inside standard - outside with exterior upgrade.

Width of climbing surface: 4 feet.

Total length of climbing surface: 20 feet.

Number of possible hold placements: 200.

Angle range: negative 5 degrees to negative 35 degrees.

Mode of control: Electro-hydraulic braking and resistance.

Electrical requirements: 9 VDC (1500ma) Plug-in transformer (supplied) or battery used.

Electronic Display: Measures distance (feet or meters), time and calories. Time and distance goals can be pre-set.

Color - frame: Anthracite Gray is standard. Custom colors available.

Color - panels: Natural Wood

Holds: Set of 36 custom training holds in 3 color groups, with optional 13 ladder Line^(tm) holds.

Maximum hold size: 2.5 inches high by 6 inches wide.

Floor Mat: 4 feet x 8 feet custom mat, 1.25 inches dual foam, black 14 oz. vinyl cover.

Warranty: Two years parts. See full warranty for details.

